



helping to defeat “improvised” threats

## 3 Steps to Deploy Detector



Step 1

Release arm strap and pivot shaft



Step 2

Lock handle and shaft into place



Step 3

Rotate search head and extend shafts

## Features

- Variable sensitivity through the selection of seven uniquely combined audio and sensitivity configurations
- Two operating modes to improve target identification
- Pinpointing mode for fast and accurate location of target
- Preconfigured sensitivity profile to assist in the detection of non-metallic conductive targets
- Fully enclosed and protected cables
- Audio and visual indications
- Vibrating Handle
- Adjustable search head
- Simple to operate
- Waterproof (IP68)
- Long lasting battery life
- Fully adjustable for operator comfort
- Optional hard case also available



## Specifications



Operating Length	1490mm / 59in - 750mm / 30in
Packed Length	397mm / 16in
Operating Weight	2.7kg / 6lbs
Transmission	V-FLEX
Audio Output	Internal Speaker Earset (Options: 1. Speaker ON / 2. Speaker OFF)
Water Resistant	IP68 (Waterproof to 3m)
Batteries	4 x C Cell (Alkaline or Rechargeable)
Visual Display	Nine LED
Battery Alarm	Visual and Audio
Operating Temperature	-30C to 60C / -22F to 140F
Design Standard	MIL STD 810 G

As a world leader in metal sensing technology, Minelab strives to continually improve its product range. Minelab reserves the right to introduce changes to the design, technical features and accessories of this product.

4907-0865-2 Brochure CM 2P A4 F3Ci EN

**COUNTERMINE**

AUSTRALIA (Head Office)  
USA  
IRELAND

Tel: +61 8 8238 0888  
Tel: +1 888 949 6522  
Tel: +353 21 423 2352  
Email: [countermine@minelab.com.au](mailto:countermine@minelab.com.au)

Fax: +61 8 8238 0890  
Fax: +1 630 401 8180  
Fax: +353 21 423 2353  
[www.minelab.com](http://www.minelab.com)

