

X-TERRA[®] PRO

Fully-Waterproof, Fully-Loaded Treasure Detector



SEARCH MODES

Park, Field and Beach

FULLY WATERPROOF

WATERPROOF TO 5 M (16 FT) — IP68

BEACH PERFORMANCE

Saltwater Capability

LIGHT AND COMPACT

1.3 kg [2.9 lb] and 63 cm [25 in]

AUDIO CONTROL

5 Audio Modes with configuration options

CHOICE OF COILS

V12X™ (Included), V8X™ & V10X™ (Accessories)

LIGHTING AND VIBRATION

Control Pod Flashlight, Red Backlight Display, Backlit Keypad, and Handgrip Vibration

LOUD AND CLEAR AUDIO

In-Built Speaker (Included), Low Latency Wireless Headphones, Wired Headphones & Waterproof Headphones (Accessories)

BUILT TO LAST

Rugged construction and up to 3-year Warranty



MINELAB
DEEP



FULLY
WATERPROOF



SIMPLE
TO USE



CONTROL POD
FLASHLIGHT



HANDGRIP
VIBRATION

POWERED BY **Pro-Switch™**
Switchable Frequency Technology

MINELAB
PERFORMANCE // IS EVERYTHING

X-TERRA[®] PRO

Fully-Waterproof, Fully-Loaded Treasure Detector

Technical Specifications

Search Modes	Park, Field, Beach
All-Metal Shortcut	Yes
Custom Search Profiles	6
Operating Frequencies [kHz]	Park and Field: 5, 10, 15 Beach: 8
Noise Cancel	Auto (19 Channels)
Ground Balance	Auto, Manual, Tracking
Sensitivity	1 to 25
Target Volume	0 to 25
Threshold Level	0 to 25
Threshold Pitch	Fixed
Target Identification [TID]	119 segment notch discrimination: Ferrous: -19 to 0 Non-ferrous: 1 to 99
Target Tones	1, 2, 5, All Tones (AT), Depth (dP)
Tone Break	Ferrous (t1)
Tone Volume	Tone 1 adjustable: 0 to 25
Recovery Speed	1 to 3
Depth Indicator	5 levels
Discrimination Segments	30 segments (in increments of 4 Target IDs)
Pinpoint Mode	Yes
Wireless Audio	Yes
Length (approx.)	Collapsed: 63 cm (25 in) Extended: 138 cm (54 in)
Weight (including batteries)	1.3 kg (2.9 lbs)
Display	Monochrome LCD
Display and Keypad Backlight (red)	Off, High, Low
Flashlight	On, Off
Vibration (Master and Ferrous)	On, Off
Supplied Coil	V12X 12" Double-D Elliptical coil with skid plate
Audio Output	In-built loudspeaker, Wired 3.5 mm (1/8") headphones, Wireless headphones
Battery	3.7 V / 5100 mAh Internal Lithium-Ion battery
Additional Included Accessories	Getting Started Guide, Charging Cable
Waterproof	5 m (16 ft) IP68
Operating Temperature Range	-10°C to +40°C (+14°F to +104°F)
Storage Temperature Range	-20°C to +70°C (-4°F to +158°F)
Key Technologies	Pro-Switch™

Equipment may vary according to the model or items ordered with your detector. Minelab reserves the right to respond to ongoing technical progress by introducing changes in design, equipment and technical features at any time. For the most up-to-date specifications for your X-TERRA[®] PRO detector, visit www.minelab.com.

What's Included



Getting Started Guide



V12X™ Coil with Skidplate
12"x9" Elliptical Double-D
– Waterproof to 5 m (16 ft)



Charging Cable

What's Available



V10X™ Coil with Skidplate
10"x7" Elliptical Double-D
– Waterproof to 5 m (16 ft)



VBX™ Coil with Skidplate
8"x5" Elliptical Double-D
– Waterproof to 5 m (16 ft)



Headphone Adaptor
6.35 mm to 3.5 mm



DC Car Charger
2 USB port car charger



Low Latency
Wireless Headphones



Waterproof
Headphones



Wired
Headphones

www.minelab.com

MINELAB[®], X-TERRA PRO[®], PRO-SWITCH[®], VBX[™], V10X[™], and V12X[™] are trademarks of Minelab Electronics Pty. Ltd. Images and graphics on this document are for illustration purposes only. Product configuration may vary from the configuration shown. Please refer to the manual for detailed operational guidance.
4907-1064-EN



PERFORMANCE // IS EVERYTHING